


4000-150P (oil-less)

Voltage	V	200	200	230	230	3x200	3x200	3x208	3x400 ²⁾	3x440 ²⁾		
Frequency	Hz	50	60	50	60	50	60	60	50	60		
Motor	HP	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0		
	kW	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2		
Displacement	l/min	352	424	352	424	352	424	424	352	424		
	CFM	12.43	14.97	12.43	14.97	12.43	14.97	14.97	12.43	14.97		
FAD @ 8 bar	l/min	180	220	180	220	180	220	220	180	220		
	CFM	6.36	7.77	6.36	7.77	6.36	7.77	7.77	6.36	7.77		
Max. pressure ¹⁾	bar	8	8	8	8	8	8	8	8	8		
	psi	120	120	120	120	120	120	120	120	120		
Max. current	A	16.4	17.6	16.0	16.6	12.8	12.8	12.8	7.2	7.2		
Tank size	litres	150	150	150	150	150	150	150	150	150		
	gallon	39.6	39.6	39.6	39.6	39.6	39.6	39.6	39.6	39.6		
Weight	kg	130	130	130	130	130	130	130	130	130		
	lbs	287	287	287	287	287	287	287	287	287		
Noise level	dB(A)/1m	70	70	70	70	70	70	70	70	70		
Thermal protection		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes		
Duty cycle		100%	100%	100%	100%	100%	100%	100%	100%	100%		



Dimensions (l x w x h)
1280 x 570 x 900 mm / 50³/₈ x 22⁴/₈ x 35³/₈ inch

- ¹⁾ Higher pressure available upon request
²⁾ Neutral is required in installation

Technical modifications reserved



JUN-AIR®

E-mail: info@jun-air.dk
Internet: www.jun-air.com